

**manroland web systems: product overview commercial printing systems**  
**manroland web systems: Produktübersicht Illustrationsdrucksysteme**

Series Baureihe	Pages Seiten (A4)	long grain short grain stehend liegend	Max. speed* (revs/h) Max. Geschwin- digkeit* (U/h)	Cylinder circumference Zylinderumfang (mm)	Max. web width Max. Bahnbreite (mm)	Running direction Laufrichtung	Blanket Gummituch	Inking system Farbwerk	Dampening system Feuchtwerk	Dyna- Change (o)	PPL®/ APL®	Folder Falzwerk	manroland web systems Inline Control systems Inline Control-Systeme					autoprnt (o)
													Inline Registration Control	InlineCutoff Control	InlineCutoff Control Dynamic	InlineDensity Control (o)	InlineFanout Control (o)	
ROTOMAN HiPrint	16	lg	55000	546 - 630	965	l - r	Conv.	Film	Hydromix	-	PPL	PFC-231	✓	✓	-	✓	-	-
ROTOMAN DirectDrive	16	lg	75000	546 - 630	965 / 1000	l - r r - l	Conv.	Film	Hydromix	✓	PPL APL (o)	PFC-131 PFC-132	✓	✓	-	✓	✓	✓
ROTOMAN S	24	lg	90000	546 - 630	1460	l - r r - l	Sleeve	Film	Hydromix	-	PPL	PFC-131 PFC-252 SFF-2 / DFF-2	✓	✓	-	✓	✓	-
ROTOMAN S	32	lg	90000	546 - 620	1830	l - r r - l	Sleeve	Film	Hydromix	-	PPL	PFC-131 PFC-252 SFF-2 / DFF-2	✓	✓	-	✓	✓	-
EUROMAN	32	lg	37500	1092 - 1260	965	l - r	Conv.	Film	Film	-	PPL	PFC-231	✓	✓	-	✓	-	-
EUROMAN	48	lg	37500	1092 - 1260	1300	l - r	Conv.	Film	Film	-	PPL	PFC-231	✓	✓	-	✓	-	-
LITHOMAN	32	lg	50000	1092 - 1260	965/1000*	l - r r - l*	Conv.	Film	Hydromix	✓	PPL APL (o)	PFC-131 PFC-252 PFC-350 SFF-2 / DFF-2	✓	✓	✓*	✓	✓	✓
LITHOMAN	32	sg	60000	890 - 940	1260 / 1320	l - r r - l	Conv.	Film	Hydromix	-	PPL	PFC-250	✓	✓	✓	✓	✓	-
LITHOMAN	40	sg	60000	890	1540	l - r r - l	Conv.	Film	Hydromix	-	PPL	PFC-250	✓	✓	✓	✓	✓	-
LITHOMAN	48	lg	50000	1092 - 1260	1460	l - r r - l	Conv.	Film	Hydromix	✓	PPL APL (o)	PFC-252 PFC-350 SFF-2 / DFF-2	✓	✓	✓	✓	✓	✓
LITHOMAN S	48	sg	70000	890 - 900	1905 / 1980	l - r r - l	Sleeve	Film	Hydromix	-	PPL APL (o)	PFC-250	✓	✓	✓	✓	✓	✓
LITHOMAN	64	lg	50000	1092 - 1260	1905	l - r r - l	Conv.	Film	Hydromix	✓	PPL APL (o)	PFC-252 PFC-350 SFF-2 / DFF-2	✓	✓	✓	✓	✓	✓
LITHOMAN S	64	sg	70000	872 - 940	2640	l - r r - l	Sleeve	Film	Hydromix	✓	PPL APL (o)	PFC-250	✓	✓	✓	✓	✓	✓
LITHOMAN	72	lg	50000	1092 - 1260	1980 / 2060	l - r r - l	Conv.	Film	Hydromix	✓	PPL APL (o)	PFC-252 PFC-350 SFF-2 / DFF-2	✓	✓	✓	✓	✓	✓
LITHOMAN	80	lg	50000	1240 - 1260	2250	l - r r - l	Conv.	Film	Hydromix	✓	PPL APL (o)	PFC-252 PFC-350 SFF-2 / DFF-2	✓	✓	✓	✓	✓	✓
LITHOMAN S	96	lg	50000	1140 - 1240	2860	l - r r - l	Sleeve	Film	Hydromix	✓	PPL APL (o)	PFC-252 PFC-350 SFF-2 / DFF-2	✓	✓	✓	✓	✓	✓

\* depending on cutoff and press configuration / abhängig von Abschnittslänge und Maschinenkonfiguration

(o): optional